

# CONCERT AUDIO



## PRICE LIST

**EFFECTIVE DATE 15 January 2012**

ALL PRICES ARE:

FULL SUGGESTED RETAIL

PER UNIT UNLESS SPECIFIED

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

FOB CAPE TOWN FREIGHT COLLECT

ARE ONLY A GUIDE DUE TO VOLATILITY OF EXCHANGE RATE

PRODUCTS ARE AVAILABLE TO ORDER

STANDARD TERMS AND CONDITIONS OF SALE APPLY

[www.communitypro.com](http://www.communitypro.com)

ERRORS AND OMISSIONS EXCEPTED

107 HUGO STREET  
GOODWOOD  
7460

PO BOX 643  
BELLVILLE  
7535

TEL +27(21) 592-5906



EMAIL: [info@concertaudio.co.za](mailto:info@concertaudio.co.za)

FAX +27(21) 592-3830

[www.concertaudio.co.za](http://www.concertaudio.co.za)

**COAXIAL CEILING LOUDSPEAKERS**

Passive 2 way coaxial, 12" loudspeakers, cast frame, 1" exit UC1 non-metallic diaphragm compression driver, vented baffle plate. Available with or without high quality transformer. Powersense™ DDP driver protection. Backbox, grille and rails sold separately.

Model	Description	Weight	Excl VAT	Incl VAT
 <b>CLOUD12-66</b>	2 way, 50 Hz - 15 kHz, 60° x 60° coverage full range coaxial loudspeaker LF 1 x 12", HF 1 x 1" compression driver 420W RMS, 600W PGM, 8 Ohm	9 Kg	R 9,000.00	R 10,260.00
 <b>CLOUD12-66T</b>	Same as CLOUD12-66 with 70V/100V transformer and switchable taps @ 200W, 100W, 50W, 25W	12 Kg	R 9,947.37	R 11,340.00
<b>CLOUD12-99</b>	2 way, 50 Hz - 15 kHz, 90° x 90° coverage full range coaxial loudspeaker LF 1 x 12", HF 1 x 1" compression driver 420W RMS, 600W PGM, 8 Ohm	9 Kg	R 9,000.00	R 10,260.00
<b>CLOUD12-99T</b>	Same as CLOUD12-99 with 70V/100V transformer and switchable taps @ 200W, 100W, 50W, 25W	12 Kg	R 9,947.37	R 11,340.00
<b>CLOUD12SUB</b>	Ceiling mount subwoofer, 45 Hz - 150 Hz 360° x 180° coverage, LF 1 x 12" 200W RMS, 500W PGM, 8 Ohm	9 Kg	R 9,000.00	R 10,260.00
<b>CLOUD12SUB-T</b>	Same as CLOUD12SUB with 70V/100V transformer and switchable taps @ 200W, 100W, 50W, 25W	12 Kg	R 9,947.37	R 11,340.00

**ACCESSORIES**

Model	Description	Weight	Excl VAT	Incl VAT
<b>C12BB3</b>	Metal backbox for CLOUD12 ceiling loudspeakers	21 Kg	R 3,157.89	R 3,600.00
<b>C12SQGRL</b>	Square white grill for CLOUD12	TBA	R 438.60	R 500.00

# COMMUNITY PRICE LIST



# CPL SERIES

Suggested Retail Price  
15-Jan-12

## SOUND REINFORCEMENT / CONTRACTOR / INSTALLATION LOUDSPEAKERS

### FULL RANGE SYSTEMS

PowerSense™ DDP, Rigging / Stand / Bracket Attachment Points, Perforated Black Steel Grilles, White Cloth Grille Covering with White Painted Versions, Coaxial HE Dome, Accepts 1/4" -20 eyebolts. Barrier Strip/Neutral-compatible Connectors (barrier strip only on 70V versions)

Model	Description	Weight	Excl VAT	Incl VAT
 <b>CPL23-B</b>	2 way, 70 Hz - 20 kHz, 90° x 90° LF 1 x 8", HF 1 " dome 100W RMS, 250W PGM, 8 Ohm Black paint, steel yoke bracket included Recommended amp for max SPL: 210W to 300W @ 8 Ohms Sensitivity 1W / 1m: 87dB SPL (80Hz - 20kHz 1/3 octave bands)	10.4 Kg	R 3,852.63	R 4,392.00
<b>CPL23-W</b>	White painted version of CPL23-B			
<b>CPL23-BT</b>	Same as CPL23-B with 70V transformer taps for 60W, 30W, 15W and 7.5W	11.3 Kg	R 4,326.32	R 4,932.00
<b>CPL23-WT</b>	White painted version of CPL23-BT			
 <b>CPL27-B</b>	2 way, 60 Hz - 20 kHz, 90° x 90° LF 2 x 8", HF 1 " dome 200W RMS, 500W PGM, 4 Ohm Black paint, steel yoke bracket included Recommended amp for max SPL: 420W to 600W @ 4 Ohms Sensitivity 1W / 1m: 86dB SPL (63Hz - 20kHz 1/3 octave bands)	15.9 kg	R 4,957.89	R 5,652.00
<b>CPL27-W</b>	White painted version of CPL27-B			
<b>CPL27-BT</b>	Same as CPL27-B with 70V transformer taps for 60W, 30W, 15W and 7.5W	16.3 Kg	R 5,589.47	R 6,372.00
<b>CPL27-WT</b>	White painted version of CPL27-BT			

### ACCESSORIES

Model	Description	Weight	Excl VAT	Incl VAT
<b>1/4EYBLTKIT</b>	Eyebolt kit for suspending / rigging, contains four 1"/25mm i.d., 1/4"-20 forged eyebolts and steel cup washers, black zinc plated	0.5 Kg	R 535.09	R 610.00

**FULL-RANGE SURFACE MOUNT LOUDSPEAKERS**

Modern architectural design, high-impact ABS plastic enclosures, weather-resistant construction, two-layer powder coated grilles, selectable 70V/100V or 8 ohm operation via front-accessible power tap switch behind a rotatable logo, Infin-A-Ball™ multi-angle wall mount bracket included

Model	Description	Weight	Excl VAT	Incl VAT
<b>DS5-B</b>	Compact, 2-way, full-range coaxial surface mount loudspeaker LF 1 x 5", HF 1 x 1", compression driver 80 Hz - 20kHz, 130° conical coverage, 93 dB SPL 1W/1m 100W RMS, 8 ohm or 70V/100V operation Powertaps (70V) 60W, 30W, 15W, 7.5W, bypass Infin-A-Ball™ multi-angle wall mounting bracket included <i>Priced as single units, sold in pairs only</i>		R 2,491.23	R 2,840.00
<b>DS5-W</b>	White version of DS5-B			

Model	Description	Weight	Excl VAT	Incl VAT
<b>DS8-B</b>	Compact, 2-way, full-range coaxial surface mount loudspeaker LF 1 x 8", HF 1 x 1.25", compression driver 70 Hz - 20kHz, 130° conical coverage, 95 dB SPL 1W/1m 150W RMS, 8 ohm or 70V/100V operation Powertaps (70V) 60W, 30W, 15W, 7.5W, bypass Infin-A-Ball™ multi-angle wall mounting bracket included <i>Priced as single units, sold in pairs only</i>		R 3,692.98	R 4,210.00
<b>DS8-W</b>	White version of DS8-B			

Model	Description	Weight	Excl VAT	Incl VAT
<b>DS8SUB-B</b>	Surface mount subwoofer system, LF 1 x 8" 60 Hz - 160 Hz, 180° x 360°, 88 dB SPL 1W/1M 200W RMS, 8 Ohm or 70V/ 100V operation Powertaps (70V) 200W, 100W, 50W, 25W, bypass Infin-A-Ball™ multi-angle wall mounting bracket included <i>Priced as single units, sold in pairs only</i>		R 4,894.74	R 5,580.00
<b>DS8SUB-W</b>				

# COMMUNITY PRICE LIST

**ENTASYS™**

Suggested Retail Price

15-Jan-12

---

## ENTASYS COLUMN LINE ARRAY SYSTEMS

---

High performance indoor / outdoor column line array systems with true line array performance to 16 kHz, modular design for versatile coverage, wide frequency range and high output level, passive design with no internal electronics, available in black or white.

---

Model	Description	Weight	Excl VAT	Incl VAT
ENT-FR	Entasys full range column LF 6 x 3.5", MF 18 x 2.35", HF 42 x 1" 200 Hz - 20 KHz, 120° H x 10° V 1500W PGM, 12 Ohms Straight flush mount wall brackets included 1130.3mm x 139.7mm x 186.94mm	21.8 Kg	R 26,842.11	R 30,600.00
ENT-LF	Entasys low frequency extension column LF 6 x 3.5", 200Hz - 1 kHz 1500W PGM, 12 Ohm Straight flush mount wall brackets included 1130.3mm x 139.7mm x 186.94mm	14.1kg	R 18,157.89	R 20,700.00

---

## ENTASYS ACCESSORIES

---

Model	Description	Excl VAT	Incl VAT
ENT-PB	Entasys Pan Bracket - allows array to panned left or right up to 160°	R 1,168.42	R 1,332.00
ENT-PT	Entasys combination pan tilt bracket	R 3,157.89	R 3,600.00
ENT-FK	Entasys fly kit bracket	R 1,831.58	R 2,088.00
ENT-CB	Entasys coupler bracket	R 1,294.74	R 1,476.00
ENT-750T	Entasys 750W autoformer	R 4,231.58	R 4,824.00

---


**iBOX "HP SERIES" PREMIUM QUALITY HIGH POWER INSTALLATION SYSTEMS**

**iBOX FULL-RANGE SYSTEMS**


Trapezoidal full-range systems of premium quality. Features include: large format 1.4" exit HF compression driver, Cast Frame Driver, Baltic birch plywood, Tuff-Coat™ finish, arrayable profile, 23 x M10 load-rated rigging points, 4 x M8 mounting points on rear panel, All iBox systems are equipped with a switchable PASSIVE/BIAMP input module. The input panel includes dual locking-type NL4 connectors and terminal strip. 2-way full range systems feature rotatable horns. An extensive range of hardware options are available. iBox systems are available in standard black and white versions. Unfinished versions may be custom ordered by special request.

**IHP3500 SERIES**

**IHP3500 SERIES: 15-INCH, 3 WAY, FULL RANGE SYSTEMS**

Model	Description	Weight	Excl VAT	Incl VAT
	<b>IHP-3594</b> 3-WAY, 80 Hz - 16 kHz, 90° H x 40° V LF 1 x 15", MF 1 x 8", HF 1 x 1.4", black Tuff-Coat™ finish 600W RMS / 1500W PGM, 8 Ohm (passive mode) MF/HF 100W/250W, LF 600W/1500W, 8 Ohm (Biamp mode) 23 x M10 rigging points, 4 x M8 for Omnimount 240 series	61.7Kg	R 32,368.42	R 36,900.00
	<b>IHP-3564</b> Same as IHP-3594 with 60° H x 40° Horn			
<b>IHP-3594P</b> <b>IHP-3564P</b>	Portable version with handles Portable version with handles		R 33,947.37	R 38,700.00

**IHP3500 SERIES: SUBWOOFER SYSTEMS**

	<b>I-118S</b> High Power Subwoofer System, 1 x 18" 42 - 100 Hz, 600W RMS / 1500W PGM, 8 Ohm Trapezoidal (Same size enclosure as IHP-3594 and IHP3564) Direct Radiator ported system, black Tuff-Coat finish 23 x M10 rigging points, 4 x M8 for Omnimount 240 series	55.3 Kg	R 20,526.32	R 23,400.00
	<b>I-215LVS</b> High Power Subwoofer System, 2 x 15" 48 - 100 Hz, 1200W RMS / 3000W PGM, 4 Ohm Trapezoidal (Same size enclosure as IHP-3594 and IHP3564) Direct Radiator ported system, black Tuff-Coat finish 23 x M10 rigging points, 4 x M8 for Omnimount 240 series	64.9 Kg	R 25,263.16	R 28,800.00


# COMMUNITY PRICE LIST

# iBOX SERIES



Suggested Retail Price  
15-Jan-12

## IHP1500 SERIES

### IHP1500 SERIES: 15-INCH, 2 WAY, FULL RANGE SYSTEMS

Model	Description	Weight	Excl VAT	Incl VAT
 IHP-1599	2-way, 45 Hz - 18 kHz, 90° H x 90° V LF 1 x 15", HF 1 x 1.4", black Tuf-Coat™ finish 600W RMS / 1500W PGM (Passive mode), 8 Ohm HF 90/180W, LF 600W/1500W, 8 Ohm (Biamp Mode) 23 x M10 rigging points, 4 x M8 for Omnimount 120 Series	50.8 Kg	R 26,052.63	R 29,700.00
IHP-1596	Same as IHP-1599 with 90° H x 60° V Horn			
IHP-1594	Same as IHP-1599 with 90° H x 40° V Horn			
IHP-1566	Same as IHP-1599 with 60° H x 60° V Horn			
IHP-1564	Same as IHP-1599 with 60° H x 40° V Horn			
IHP-1544	Same as IHP-1599 with 40° H x 40° V Horn			
IHP-1526	Same as IHP-1599 with 120° H x 60° V Horn			
IHP Portable	Portable version with handles		R 27,631.58	R 31,500.00

### IHP1500 SERIES: SUBWOOFER SYSTEMS

Model	Description	Weight	Excl VAT	Incl VAT
 I-115S	High Power Subwoofer System, 1 x 15" 45 - 100 Hz, 600W RMS / 1500W PGM, 8 Ohm Trapezoidal (same size as 15" 2-Way 1500 series) Direct radiator ported system, black Tuf-Coat™ finish 23 x M10 rigging points, 4 x M8 for Omnimount 120 Series	46.7 kg	R 19,736.84	R 22,500.00
 I-215S	High Power Subwoofer System, 2 x 15" 55 - 100 Hz, 1200W RMS / 3000W PGM, 4 Ohm Trapezoidal (same size as 15" 2-Way 1500 series) Direct radiator ported system, black Tuf-Coat™ finish 23 x M10 rigging points, 4 x M8 for Omnimount 120 Series	56.7 kg	R 24,473.68	R 27,900.00
	Available in black or white			


# COMMUNITY PRICE LIST

# iBOX SERIES


Suggested Retail Price  
15-Jan-12

## IHP1200 SERIES

### IHP1200 SERIES: 12-INCH, 2 WAY, FULL RANGE SYSTEMS

Model	Description	Weight	Excl VAT	Incl VAT	
	<b>IHP-1299</b>	2-way, 60 Hz - 18 kHz, 90° H x 90° V LF 1 x 12", HF 1 x 1.4", black Tuf-Coat™ finish 600W RMS / 1500W PGM (Passive mode), 8 Ohm HF 90/180W, LF 600W/1500W, 8 Ohm (Biamp Mode) 23 x M10 rigging points, 4 x M8 for Omnimount 120 Series	44.4 Kg	R 23,684.21	R 27,000.00
	<b>IHP-1296</b>	Same as IHP-1299 with 90° H x 60° V Horn			
	<b>IHP-1294</b>	Same as IHP-1299 with 90° H x 40° V Horn			
	<b>IHP-1266</b>	Same as IHP-1299 with 60° H x 60° V Horn			
	<b>IHP-1264</b>	Same as IHP-1299 with 60° H x 40° V Horn			
	<b>IHP-1244</b>	Same as IHP-1299 with 40° H x 40° V Horn			
	<b>IHP-1226</b>	Same as IHP-1299 with 120° H x 60° V Horn			
<b>IHP 12 Portable</b>	Portable version - with handles		R 25,263.16	R 28,800.00	

### IHP1200 SERIES: SUBWOOFER SYSTEMS

Model	Description	Weight	Excl VAT	Incl VAT	
	<b>I-112S</b>	High Power Subwoofer System, 1 x 12" 30 - 100 Hz, 600W RMS / 1500W PGM, 8 Ohm Trapezoidal (same size as 12" 2-Way 1200 series) Direct radiator ported system, black Tuf-Coat™ finish 23 x M10 rigging points, 4 x M8 for Omnimount 120 Series	40.8 Kg	R 18,947.37	R 21,600.00
	<b>I-212S</b>	High Power Subwoofer System, 2 x 12" 35 - 100 Hz, 1200W RMS / 3000W PGM, 4 Ohm Trapezoidal (same size as 12" 2-Way 1200 series) Direct radiator ported system, black Tuf-Coat™ finish 23 x M10 rigging points, 4 x M8 for Omnimount 120 Series	56.7 kg	R 23,684.21	R 27,000.00
	Available in black or white				

## i2W8

### i2W8: DUAL 8 - INCH, TWO WAY, FULL RANGE MULTIPURPOSE / UNDERBALCONY SYSTEM

Model	Description	Weight	Excl VAT	Incl VAT
<b>i2W8</b>	Two way, 65 Hz - 16kHz, 120° H x 60° V LF 2 x 8" carbon fibre, HF 1 x 1" compression driver 250W RMS, 600W PGM, 8 Ohm 6 x M10 rigging points, black or white finish Steel yoke bracket included	24.5 Kg	R 19,421.05	R 22,140.00
<b>i2W8T</b>	Same as i2W8T with built in 200W autoformer for 70/100V lines with selectable taps @ 200W, 100W, 50W, 25W	25.9 K8	R 20,052.63	R 22,860.00

# COMMUNITY PRICE LIST

# iBOX SERIES

Suggested Retail Price  
15-Jan-12


## IBOX ACCESSORIES AND MOUNTING BRACKETS

Installation brackets for the iBox Series are available in black or white powder coated steel finishes. All mounting hardware included

Model	Description	Weight	Excl VAT	Incl VAT
IB-Y35	Installation Bracket - Yoke iHP3500 Series	9.1Kg	R 2,903.51	R 3,310.00
IB-Y15	Installation Bracket - Yoke iHP1500 Series	8.2 Kg	R 2,780.70	R 3,170.00
IB-Y12	Installation Bracket - Yoke iHP1200 Series	7.3Kg	R 2,649.12	R 3,020.00
IB-VY35	Installation Bracket - Vertical Yoke iHP3500 Series	15 Kg	R 4,359.65	R 4,970.00
IB-VY15	Installation Bracket - Vertical Yoke iHP1500 Series	13.2 Kg	R 4,201.75	R 4,790.00
IB-VY12	Installation Bracket - Vertical Yoke iHP1200 Series	11.3 Kg	R 4,043.86	R 4,610.00
IB-TPK	Installation Bracket - Tight Pack Kit	4.5 Kg	R 1,894.74	R 2,160.00
IB-VTK	Installation Bracket - Vari Tilt Kit	4.1 Kg	R 6,000.00	R 6,840.00
IB-VAK	Installation Bracket - Vari Angle Kit	3.2 Kg	R 2,587.72	R 2,950.00
IB-UPK	Installation Bracket - Universal Planar Kit	15.4Kg	R 7,736.84	R 8,820.00
IB-HFK	Installation Bracket - Horizontal Fly Kit	11.3Kg	R 6,403.51	R 7,300.00
IB-VFK	Installation Bracket - Vertical Fly Kit	6.4 Kg	R 3,850.88	R 4,390.00
M10EYEBLTKIT	10mm Eyebolt kit - consist of 4 x M10 forged eyebolts	0.5 Kg	R 596.49	R 680.00
STKIT	Seat Track Kit for suspending a single loudspeaker Consists seat track channels for both M10 and 3/8-16"	0.5Kg	R 596.49	R 680.00

## LF SERIES- LOW FREQUENCY SUBWOOFER SYSTEMS

Low frequency dual 18" subwoofer systems for permanent installations. Active air and vented pole cooling

Model	Description	Weight	Excl VAT	Incl VAT
 <b>IIf218B</b>	Dual 18" Low Frequency Subwoofer System 40 Hz - 125 Hz, 1600W RMS / 4000W PGM, 4 Ohm Active Air and vented pole cooling TuffCoat finish. For Permanent installation	103.9 Kg	R 38,368.42	R 43,740.00



# COMMUNITY PRICE LIST

# M-CLASS

Suggested Retail Price  
15-Jan-12

## M-CLASS M12 STAGE MONITOR - *For the most demanding clients*

10-1/2 inches / 26.7 cm high, low profile, multi-layer glass composite construction, non-reflective Tuf-Coat™ exterior, Unique hidden handles and lift points, cable management system. Mirror image left or right versions available.

Model	Description	Weight	Excl VAT	Incl VAT
<b>M12R-BP</b>	12", 2 way stage monitor, black finish with handles Coverage: Horizontal 40°-90° asymmetrical vertical 70° 55 Hz - 18 kHz, LF 1 x 12", HF 1 x 2" Exit (Passive) 300W RMS, 750W PGM, 8 Ohm LF: 300W RMS, 750W PGM, 8 Ohm HF: 90W RMS, 160W PGM, 8 Ohm Switchable Biamp/Passive configuration. HF Horn moulded into the faceplate to the right of the LF driver	29.5 Kg	R 30,789.47	R 35,100.00
				
				
<b>M12R-WP</b>	White version of M12R-B			
<b>M12L-BP</b>	Same as M12R-B, with the HF horn moulded into the faceplate to the left of the LF driver			
<b>M12L-WP</b>	White version of M12L-B			

## MX41 PORTABLE MONITOR SYSTEM

Baltic Birch enclosures, Tuf-Coat™ Finish, PowerSense™ DDP, Biampable, Neutrik and 1/4" Connectors, Heavy-Duty Rubber Feet

Model	Description	Weight	Excl VAT	Incl VAT
<b>MX41-94B</b>	2-way Multi-Angle Enclosure, 70 Hz - 18 kHz, 80° H x 35° V LF 1 x 12", HF 1 x 1" Compression Driver (Passive) 200W RMS, 500W PGM, 8 Ohm (Biamp) LF 200W RMS, 500W PGM, 8 Ohm, HF 50W RMS, 125W PGM, 8 Ohm Sensitivity: 97 dB SPL	26.3 Kg	R 14,368.42	R 16,380.00
<b>MX41-94W</b>	White version of MX41-94B with white cloth over grill			
<b>MX41-64B</b>	Same as MX41-94B except with 50° H x 35° V Horn			
<b>MX41-64W</b>	White version of MX41-64B with white cloth over grill			

---

**MX8 AND MX10 COMPACT COAXIAL MONITORS**

Stylish and compact appearance , birch plywood enclosure, black or white painted finish, single ergo grip rear pocket handle, DYNA-TEC driver protection system, Carbon Ring Cone Technology, two paralleled NL4-compatible locking connectors internally looped to one 2 terminal barrier strip

---

<b>Model</b>	<b>Description</b>	<b>Weight</b>	<b>Excl VAT</b>	<b>Incl VAT</b>
<b>MX10-B</b>	10 inch, 2 way compact coaxial monitor LF 1 x 10", HF 1 x 1.25" 200W RMS, 500W PGM, 8 Ohm, 100° conical Sensitivity: 99 dB SPL	12.2 Kg	R 6,850.88	R 7,810.00
<b>MX10-W</b>	White version of MX10-B			
<b>MX8-B</b>	8 inch, 2 way compact coaxial monitor LF 1 x 8", HF 1 x 1.25" 150W RMS, 375W PGM, 8 Ohm, 115° conical Sensitivity: 96 dB SPL	9.5 Kg	R 5,903.51	R 6,730.00
<b>MX8-W</b>	White version of MX8-B			

---

**ACCESSORIES**

<b>Model</b>	<b>Description</b>	<b>Weight</b>	<b>Excl VAT</b>	<b>Incl VAT</b>
<b>M12-RDCASE2</b>	Black ATA Case to hold two (2) single M12 stage monitors. Four recessed latches, eight recessed handles, accessory compartment, 4" castors. 775mm H x 775mm W x 762mm D	46.2 Kg	R 20,175.44	R 23,000.00
<b>M12-RDCASE4</b>	Black ATA Case to hold four (4) single M12 stage monitors. Four recessed latches, eight recessed handles, accessory compartment, 4" castors. 775mm H x 1207mm W x 762mm D	72.5 Kg	R 31,578.95	R 36,000.00

---

# COMMUNITY PRICE LIST

# R-SERIES






Suggested Retail Price

15-Jan-12

## ALL WEATHER / ALL PURPOSE SOUND REINFORCEMENT / PLAYBACK LOUDSPEAKERS


### R2 THREE WAY FULL RANGE DEFINED COVERAGE WEATHER RESISTANT SYSTEMS

Multi Layer Glass Composite Construction, Passive Crossover with DYNA-TECH driver protection, All Horn Loaded, High Fidelity, 3-Layer Weather-Stop™ Stainless Steel Grille, Five 1/2"-13 Mounting Points, Gland Nut with 3.6m SJOW Input Cable, SSYR2 mounting bracket sold separately, R2-X weather resistant models feature light grey colour enclosures and silver stainless steel grille. Five year transferable warranty / Fifteen year enclosure warranty. Includes mounting yoke bracket

Model	Description	Weight	Excl VAT	Incl VAT
 <b>R2-52Z</b>	3 way long throw, 70 Hz - 16 kHz, 50° H x 20° V LF 2 x12", MF 2 x 2" M200, HF 1 x 1" compression driver 400 W RMS, 1000W PGM, 4 Ohm	56.7 Kg	R 39,412.28	R 44,930.00
 <b>R2-77Z</b>	3 way short throw, 70 Hz - 16 kHz, 60° H x 60° V LF 2 x12", MF 1 x 2" M200, HF 1 x 1" compression driver 400 W RMS, 1000W PGM, 4 Ohm	50.3 Kg	R 34,482.46	R 39,310.00
 <b>R2-94Z</b>	3 way short throw, 70 Hz - 16 kHz, 80° H x 40° V LF 2 x12", MF 1 x 2" M200, HF 1 x 1" compression driver 400 W RMS, 1000W PGM, 4 Ohm	50.3 Kg	R 34,482.46	R 39,310.00
 <b>R2-474Z</b>	3 way medium throw, 70 Hz - 16 kHz, 40°-70° H x 40° V LF 2 x12", MF 1 x 2" M200, HF 1 x 1" compression driver 400 W RMS, 1000W PGM, 4 Ohm Asymmetrical coverage	50.3 Kg	R 34,482.46	R 39,310.00
 <b>R2-694Z</b>	3 way medium throw, 70 Hz - 16 kHz, 60°-90° H x 40° V LF 2 x12", MF 1 x 2" M200, HF 1 x 1" compression driver 400 W RMS, 1000W PGM, 4 Ohm Asymmetrical coverage	50.3 Kg	R 34,482.46	R 39,310.00

### R2 WEATHER RESISTANT INDOOR/OUTDOOR SUBWOOFER SYSTEM

Multi Layer Glass Composite Construction, DYNA-TECH protection circuitry, patented Cool-Coil drivers, All Horn Loaded 3-Layer Weather-Stop™ Stainless Steel Grille, Five 1/2"-13 Mounting Points, Gland Nut with 3.6m SJOW Input Cable, light grey colour enclosure and silver stainless steel grille. Five year transferable warranty / Fifteen year enclosure warranty. Five year transferable warranty / Fifteen year enclosure warranty. Includes mounting bracket

Model	Description	Weight	Excl VAT	Incl VAT
 <b>R2SUB</b>	Vented Subwoofer, 30Hz - 500Hz LF 2 x12" 400 W RMS, 1000W PGM, 4 Ohm	41.3 Kg	R 31,421.05	R 35,820.00




# COMMUNITY PRICE LIST

# R-SERIES

Suggested Retail Price  
15-Jan-12



## R1 TWO FULL-RANGE WEATHER RESISTANT OUTDOOR / INDOOR SYSTEMS

Multi Layer Glass Composite Construction, Passive Crossover with Powersense™ DDP, All Horn Loaded, High Fidelity, 3-Layer Weather-Stop™ Stainless Steel Grille, Five 1/2"-13 Mounting Points, Gland Nut with 3.6m SJOW Input Cable, SSYR1 mounting bracket sold separately, R1-Z weather resistant models feature light grey colour enclosures and silver stainless steel grille  
Five year transferable warranty / Fifteen year enclosure warranty. Mounting bracket included

Model	Description	Weight	Excl VAT	Incl VAT
 <b>R1-94Z</b>	2 way system, 90 Hz - 16 kHz, 80° H x 35° V LF 1 x 12", HF 1 x 1" compression driver 200W RMS, 500W PGM, 8 Ohm	34.9 Kg	R 24,157.89	R 27,540.00
 <b>R1-66Z</b>	2 way system, 90 Hz - 16 kHz, 60° H x 60° V LF 1 x 12", HF 1 x 1" compression driver 200W RMS, 500W PGM, 8 Ohm	34.9 Kg	R 24,157.89	R 27,540.00
 <b>R1-64Z</b>	2 way system, 90 Hz - 16 kHz, 50° H x 35° V LF 1 x 12", HF 1 x 1" compression driver 200W RMS, 500W PGM, 8 Ohm	34.9 Kg	R 24,157.89	R 27,540.00
<b>R1-94BNG</b>	Same as R1-94X, black colour shell, no grille	33.1 Kg	R 22,578.95	R 25,740.00
<b>R1-66BNG</b>	Same as R1-66X, black colour shell, no grille			
<b>R1-64BNG</b>	Same as R1-64X, black colour shell, no grille			

## RMG/RSH - VOICE-RANGE/ANNOUNCEMENT LOUDSPEAKERS - COMPLETE HORN AND DRIVER SYSTEMS

Multi Layer Glass Composite Construction, High Sensitivity Horn Loaded Voice / Tone Signalling Loudspeaker Packages Utilizing Community's High Output Compression Driver Technology. Light Gray Colour, High Output, Low Distortion M200A.  
Five year transferable warranty / 15 year enclosure warranty

Model	Description	Weight	Excl VAT	Incl VAT
 <b>RMG200A</b>	Voice Range Horn System 50° H x 40° V, 400 Hz - 4700 Hz 1 x 2" M200A driver 75W RMS, 120W PGM, 8 Ohm	10.9 Kg	R 12,473.68	R 14,220.00
<b>RMG200AT</b>	Same as MG200A with 200W autoformer 70V/100V lines with multiple taps @ 200W, 100W, 50W  Stainless Steel Bracket included	11.8 Kg	R 13,105.26	R 14,940.00
 <b>RSH462</b>	Exponential Focused Array™ Horn System Complete horn/driver system including four M200A drivers, 400 Hz - 8 kHz 300W RMS, 750W PGM, 8 Ohm Factory installed mounting bracket fully assembled and attached to loudspeaker	38.6 Kg	R 30,789.47	R 35,100.00







# COMMUNITY PRICE LIST

# R-SERIES

Suggested Retail Price  
15-Jan-12

## R.5 COMPACT FULL RANGE WEATHER RESISTANT SYSTEMS

Weather/UV-Resistant and Durable Rotomolded Construction, Passive Crossover With PowerSense™ DDP, All Horn Loaded, High Fidelity, Five 3/8"-16 Mounting Points, Gland Nut With 3.6m SJOW Input Cable, Light Gray or Black Colour. All R.5 models include a Weather Stop™ Stainless Steel Silver Grille and Stainless Steel Mounting Yoke. 5 year transferable warranty / 15 year enclosure warranty

Model	Description	Weight	Excl VAT	Incl VAT
 <b>R.5-66Z</b>	2-way system, 85 Hz - 16 kHz, 50° H x 50° V LF 1 x 12", HF 1 x 1" compression driver 200W RMS, 500W PGM, 8 Ohm	18.1 Kg	R 12,000.00	R 13,680.00
<b>R.5-66TZ</b>	Same as R.5-66Z with 200W autoformer and switchable taps @ 25W, 50W, 100W, and 200W	19 Kg	R 12,947.37	R 14,760.00
 <b>R.5-94Z</b>	2-way system, 85 Hz - 16 kHz, 90° H x 40° V LF 1 x 12", HF 1 x 1" compression driver 200W RMS, 500W PGM, 8 Ohm	17.7 Kg	R 12,000.00	R 13,680.00
<b>R.5-94TZ</b>	Same as R.5-94Z with 200W autoformer and switchable taps @ 25W, 50W, 100W, and 200W	18.6 Kg	R 12,947.37	R 14,760.00
 <b>R.5-99Z</b>	2-way system, 85 Hz - 16 kHz, 90° H x 90° V LF 1 x 12", HF 1 x 1" compression driver 200W RMS, 500W PGM, 8 Ohm	17.7 Kg	R 12,000.00	R 13,680.00
<b>R.5-99TZ</b>	Same as R.5-99Z with 200W autoformer and switchable taps @ 25W, 50W, 100W, and 200W	18.6 Kg	R 12,947.37	R 14,760.00
 <b>R.5COAX-66</b>	2-way system, 80 Hz - 18 kHz, 60° H x 60° V LF 1 x 12", HF 1 x 1" exit 200W RMS, 500W PGM, 8 Ohm	19.1 Kg	R 12,000.00	R 13,680.00
<b>R.5-COAX-66T</b>	Same as R.5COAX-66 with 200W/70V transformer and switchable taps @ 25W, 50W, 100W, and 200W	21.8 Kg	R 12,947.37	R 14,760.00
 <b>R.5COAX-99</b>	2-way system, 80 Hz - 18 kHz, 90° H x 90° V LF 1 x 12", HF 1 x 1" exit 200W RMS, 500W PGM, 8 Ohm	19.1 Kg	R 12,000.00	R 13,680.00
<b>R.5-COAX-99T</b>	Same as R.5COAX-99 with 200W/70V transformer and switchable taps @ 25W, 50W, 100W, and 200W	21.8 Kg	R 12,947.37	R 14,760.00
 <b>R.5-SUB</b>	Compact Subwoofer, 45Hz - 150Hz LF 1 x 12", 120Hz Internal low pass filter 200W RMS, 500W PGM, 68 Ohms	19.9Kg	R 12,000.00	R 13,680.00
<b>R.5-SUBT</b>	Same as R.5-SUB with 200W/70V transformer and switchable taps @ 25W, 50W, 100W, and 200W	21.8 Kg	R 12,947.37	R 14,760.00


# COMMUNITY PRICE LIST

# R-SERIES

Suggested Retail Price  
15-Jan-12

## R.25 COMPACT FULL RANGE WEATHER RESISTANT SYSTEMS

Weather/UV-Resistant and Durable Rotomolded Construction, Passive Crossover With Dyna-Tech protection, High Fidelity, Five 3/8"-16 Mounting Points, Gland Nut With 3.6m SJOW Input Cable, Light Gray. All R.25 models include a Weather Stop™ Stainless Steel Silver Grille and Stainless Steel Mounting Yoke. 5 year transferable warranty / 15 year enclosure warranty

Model	Description	Weight	Excl VAT	Incl VAT
 <b>R.25-94Z</b>	2-way system, 100 Hz - 16 kHz, 90° H x 40° V LF 1 x 8", HF 1 x 3/4" compression driver 200W RMS, 500W PGM, 8 Ohm	10.7 Kg	R 6,473.68	R 7,380.00
<b>R.25-94TZ</b>	Same as R.25-94Z with 200W Autoformer and switchable taps @ 25W, 50W, 100W, and 200W	11.7 Kg	R 7,105.26	R 8,100.00
<b>R.25-94BZ</b>	Same as R.25-94Z with black enclosure, black grill and bracket		R 6,473.68	R 7,380.00
<b>R.25-94BTZ</b>	Same as R.25-TZ with black enclosure, black grill and bracket		R 7,105.26	R 8,100.00
<b>R.25-94WZ</b>	Same as R.25-94Z with white enclosure, white grill and bracket		R 6,473.68	R 7,380.00
<b>R.25-94WTZ</b>	Same as R.25-94Z with white enclosure, white grill and bracket		R 7,105.26	R 8,100.00


# COMMUNITY PRICE LIST

# R-SERIES

Suggested Retail Price  
15-Jan-12


## R.5HP HIGH OUTPUT COMPACT FULL RANGE WEATHER RESISTANT SYSTEM

Weather/UV-Resistant and Durable Rotomolded Construction, Passive Crossover With PowerSense™ DDP, All Horn Loaded, High Fidelity, Five 3/8"-16 Mounting Points, Gland Nut With 3.6m SJOW Input Cable, Light Gray Colour. All R.5HP models include a Weather Stop™ Stainless Steel Silver Grille and Stainless Steel Mounting Yoke. 5 year transferable warranty / 15 year enclosure warranty

Model	Description	Weight	Excl VAT	Incl VAT
 R.5HP	3-way system, 85 Hz - 16 kHz, 60° H x 40° V LF 1 x 12", MF 1 x M200 2", HF 1 x 1" compression driver 200W RMS, 500W PGM, 6 Ohm	22.2 Kg	R 19,105.26	R 21,780.00
R.5HPT	Same as R.5HP with 200W/70V transformer and switchable taps @ 25W, 50W, 100W, and 200W	23.1 Kg	R 20,052.63	R 22,860.00


## R6-51 FULL RANGE ARRAYABLE WEATHER RESISTANT SYSTEM

Multi Layer Glass Composite Construction, High Sensitivity Horn Loaded 3 way System, 3 Layer Weather Stop™ Black Grille, 1/2"-13 Mounting Points, Light Gray Colour, 3.6m SJOW Input Cable. Electronic Cross Over Required. 5 year transferable warranty / 15 year enclosure warranty. Electronic crossover required

Model	Description	Weight	Excl VAT	Incl VAT
 R6-51BIAMP	3 way full-range, biamp 50 Hz - 16 kHz LF 6 x 12", MF 6 x 2" M200, HF 6 x 1" compression driver 50° H x 10° V, LF 1200W RMS @ 5.3 Ohm, MF 450W RMS @ 8 Ohm, HF 300W RMS @ 8 Ohm Available to order only - extended lead time	174.2 Kg	R 139,736.84	R 159,300.00

## R6-BASS HORN ARRAYABLE LOW FREQUENCY, WEATHER RESISTANT SYSTEM



Multi Layer Glass Composite Construction, High Sensitivity Horn Loaded, Compliments R2 and M4 Systems, 3 Layer Weather Stop™ Black Grille 1/2"-13 Mounting Points, Light Gray Colour, 3.6m SJOW Input Cable. Electronic Cross Over Required.

Model	Description	Weight	Excl VAT	Incl VAT
 R6-BASSHORN	Bass Horn, 6 x 12", 45Hz - 500Hz 1200W RMS, 3000W PGM, 5.3 Ohm Available to order only	122 Kg	R 86,842.11	R 99,000.00

**HIGH OUTPUT SOUND REINFORCEMENT LOUDSPEAKERS**

**SLS FULL-RANGE HORN LOADED SYSTEMS**

Trapezoidal Baltic Birch Enclosure, Wave Coherent™, Biampable, Powersense™ DDP, Neutrik and Dual Banana Connectors, 8 x 3/8"-16 Load Rated Rigging Points. Black, White and Unpainted Versions. Electronic System Controller Required.

Model	Description	Weight	Excl VAT	Incl VAT	
	<b>SLS960</b>	3-way, 75 Hz - 18 kHz, 65° H x 50° V LF 2 x 10", MF 1 x 2" M200, HF 1 x 1"VHF100 400W RMS, 1000W PGM, 8 Ohm Black Painted version with handles	70.3 Kg	R 54,473.68	R 62,100.00
	<b>SLS960WHT</b>	White painted version of SLS960, no handles			
	<b>SLS960U</b>	Unpainted version, requires additional finishing, no handles			
	<b>SLS920</b>	3-way, 90 Hz - 18 kHz, 65° H x 50° V LF 2 x 8", MF 1 x 2" M200, HF 1 x 1"VHF100 200W RMS, 500W PGM, 8 Ohm Black Painted version with handles	39.5 Kg	R 37,105.26	R 42,300.00
	<b>SLS920WHT</b>	White painted version of SLS920, no handles			
	<b>SLS920U</b>	Unpainted version, requires additional finishing, no handles			
	<b>SLS920H</b>	Same as SLS920 with HF horn rotated 90° so HF pattern is 65° H x 50° V when system is horizontally mounted Black Painted version with handles			
	<b>SLS920HWHT</b>	White painted version of SLS920H, no handles			
	<b>SLS920HU</b>	Unpainted version, requires additional finishing, no handles			

# COMMUNITY PRICE LIST


# SOLUTIONS™ SERIES

Suggested Retail Price

15-Jan-12

## SBS VENTED SUBWOOFER

Baltic Birch Enclosure with 8 x 3/8"-16 Load Rated Rigging Points, Neutrik and Dual Banana Connectors, Cast Frame Drivers. Black, white painted and unfinished versions. Electronic System Controller Required.

Model	Description	Weight	Excl VAT	Incl VAT
 <b>SBS45</b>	Subwoofer, 27 Hz - 150 Hz 4 x 15", 2,400W RMS, 6000W PGM, 8 Ohm Use with, SLS960 and SLS920 Black Painted version with handles	113.4 Kg	R 53,526.32	R 61,020.00
<b>SBS45WHT</b>	White painted version of SBS45, no handles			
<b>SBS45U</b>	Unpainted version, requires additional finishing, no handles			





## ACCESSORIES

Model	Description	Weight	Excl VAT	Incl VAT
<b>3/8EYBLTKIT</b>	Eyebolt kit for suspending / rigging, contains four 1"/25mm i.d., 3/8"-16 forged eyebolts and steel cup washers, black zinc plated	0.5 Kg	R 631.58	R 720.00

**SOUND REINFORCEMENT / MUSICIAN / DJ FGM LOUDSPEAKERS**



**FULL RANGE SYSTEMS**

11 Ply Birch enclosure Dyna-tech driver protection system, Ferrofluid-cooled HF driver, carbon ring cone LF, 16 gauge perforated steel grille, 4 mounting for Omnimount 120 inserts, Ergo Grip handles, 2 1/4" jacks and two locking connectors (NL4 type)

Model	Description	Weight	Excl VAT	Incl VAT
<b>S-1296</b> 	2-way multi-angle enclosure, 60Hz - 20kHz LF 1 x 12", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, 8-M10 hang points, black paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 99 dB SPL (100 Hz - 10000 Hz 1/3 octave bands)	21.1 Kg	R 7,263.16	R 8,280.00
<b>S-1596</b> 	2-way, 50Hz - 20kHz LF 1 x 15", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, 8-M10 hang points, black paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 102 dB SPL (100 Hz - 10000 Hz 1/3 octave bands)	27 Kg	R 8,368.42	R 9,540.00
<b>S-3294</b> 	3-way, 60Hz - 20kHz LF 1 x 12", MF 1 x 6.5", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, 8-M10 hang points, black paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 100 dB SPL (100 Hz - 12500 Hz 1/3 octave bands)	29.3 Kg	R 9,157.89	R 10,440.00
<b>S-3594</b> 	3-way, 55Hz - 20kHz LF 1 x 15", MF 1 x 6.5", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, 8-M10 hang points, black paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 101 dB SPL (100 Hz - 12500 Hz 1/3 octave bands)	32.2 Kg	R 9,947.37	R 11,340.00

**SUBWOOFER SYSTEMS**

11 Ply Birch enclosure Dyna-tech driver protection system, Patented Cool-Coil LF Drivers, 16 gauge perforated steel Grille Ergo Grip handles, 2 1/4" jacks and two locking connectors (NL4 type)

Model	Description	Weight	Excl VAT	Incl VAT
<b>S-215S</b> 	Subwoofer, 30Hz - 2 kHz 2 x 15" 400W RMS, 1000W PGM, 4 Ohm 8 - M10 hang points, black paint finish Recommended amp for maximum SPL: 830W to 1200W @ 4 Ohms Sensitivity 1W/1m: 97 dB SPL (50 Hz - 160 Hz 1/3 octave bands)	47.2Kg	R 13,105.26	R 14,940.00
<b>S-218S</b> 	Subwoofer, 30Hz - 1 kHz 2 x 18" 600W RMS, 1500W PGM, 4 Ohm 8 - M10 hang points, black paint finish Recommended amp for maximum SPL: 1250W to 1800W @ 4 Ohms Sensitivity 1W/1m: 100 dB SPL (50 Hz - 160 Hz 1/3 octave bands)	65.3 Kg	R 18,631.58	R 21,240.00

**S SERIES ACCESSORIES**

Model	Description	Weight	Excl VAT	Incl VAT
-------	-------------	--------	----------	----------

# COMMUNITY PRICE LIST

# VERIS SERIES

Suggested Retail Price

15-Jan-12

## VERSATILE INSTALLATION LOUDSPEAKERS / SOUND REINFORCEMENT

### COMPACT FULL RANGE SYSTEMS

Compact 11 Ply Birch enclosure Dyna-Tech driver protection system, Ferrofluid-cooled HF driver, carbon ring cone LF, 16 gauge foam backed steel grille, 9 - M6 hang points, 4 Omnimount 30 bolt pattern, Steel yoke bracket allowing 0°, 10°, and 20° angles included Barrier strip/NL4 compatible locking connectors

Model	Description	Weight	Excl VAT	Incl VAT
<b>VERIS6</b>	2-way, 100Hz - 18kHz, 90° x 70° LF 1 x 6", HF 1 x ¾", 100W RMS, 250W PGM 8 Ohm, black or white paint finish, steel yoke bracket incl Recommended amp for maximum SPL: 210 to 300W @ 8 Ohms Sensitivity 1W/1m: 90 dB SPL (125 Hz - 10000 Hz 1/3 octave bands)	10.2 Kg	R 4,263.16	R 4,860.00
<b>VERIS6T</b>	Same as VERIS6 with 200W autoformer Taps for 100W, 50W, 25W, 12.5W	11.6 Kg	R 4,736.84	R 5,400.00

Model	Description	Weight	Excl VAT	Incl VAT
<b>VERIS8</b>	2-way, 90Hz - 18kHz, 90° x 70° LF 1 x 8", HF 1 x ¾", 150W RMS, 375W PGM 8 Ohm, black or white paint finish, steel yoke bracket incl Recommended amp for maximum SPL: 310 to 450W @ 8 Ohms Sensitivity 1W/1m: 91 dB SPL (125 Hz - 10000 Hz 1/3 octave bands)	13 Kg	R 4,736.84	R 5,400.00
<b>VERIS8T</b>	Same as VERIS8 with 200W autoformer Taps for 100W, 50W, 25W, 12.5W	14.3 Kg	R 5,210.53	R 5,940.00

Model	Description	Weight	Excl VAT	Incl VAT
<b>VERIS26</b>	2-way, 70Hz - 18kHz, 90° x 70° LF 2 x 6", HF 1 x ¾", 200W RMS, 500W PGM 4 Ohm, black or white paint finish, steel yoke bracket incl Recommended amp for maximum SPL: 420 to 600W @ 4 Ohms Sensitivity 1W/1m: 92 dB SPL (125 Hz - 10000 Hz 1/3 octave bands)	15 Kg	R 5,684.21	R 6,480.00
<b>VERIS26T</b>	Same as VERIS26 with 200W autoformer Taps for 200W, 100W, 50W, 25W	16.6 Kg	R 6,157.89	R 7,020.00

Model	Description	Weight	Excl VAT	Incl VAT
<b>VERIS28</b>	2-way, 70Hz - 18kHz, 90° x 70° LF 2 x 8", HF 1 x ¾", 300W RMS, 750W PGM 4 Ohm, black or white paint finish, steel yoke bracket incl Recommended amp for maximum SPL: 630 to 900W @ 4 Ohms Sensitivity 1W/1m: 93 dB SPL (125 Hz - 10000 Hz 1/3 octave bands)	18.4Kg	R 6,157.89	R 7,020.00
<b>VERIS28T</b>	Same as VERIS28 with 200W autoformer Taps for 200W, 100W, 50W, 25W, 12.5W	11.6 Kg	R 6,631.58	R 7,560.00

# COMMUNITY PRICE LIST

# VERIS SERIES

Suggested Retail Price

15-Jan-12

## VERSATILE INSTALLATION LOUDSPEAKERS / SOUND REINFORCEMENT

### FULL RANGE SYSTEMS

11 Ply Birch enclosure Dyna-Tech driver protection system, Ferrofluid-cooled HF driver, carbon ring cone LF, 16 gauge foam backed steel grille, 13 - M10 hang points, 4 Omnimount 60 bolt pattern, barrier strip / NL4 compatible locking connectors

Model	Description	Weight	Excl VAT	Incl VAT
<b>VERIS12-64</b>	2-way, 60Hz - 18kHz, 60° x 40° LF 1 x 12", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 99 dB SPL (125 Hz - 12500 Hz 1/3 octave bands)	21.1 Kg	R 7,736.84	R 8,820.00
<b>VERIS12-96</b>	2-way, 60Hz - 18kHz, 90° x 60° LF 1 x 12", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 97 dB SPL (125 Hz - 12500 Hz 1/3 octave bands)	21.1 Kg	R 7,736.84	R 8,820.00
<b>VERIS15-64</b>	2-way, 60Hz - 18kHz, 60° x 40° LF 1 x 15", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 100 dB SPL (125 Hz - 12500 Hz 1/3 octave bands)	27 Kg	R 8,842.11	R 10,080.00
<b>VERIS15-96</b>	2-way, 60Hz - 18kHz, 90° x 60° LF 1 x 15", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 99 dB SPL (125 Hz - 12500 Hz 1/3 octave bands)	27 Kg	R 8,842.11	R 10,080.00
<b>VERIS32-64</b>	3-way, 60Hz - 18kHz, 60° x 40° LF 1 x 12", MF 1 x 6.5", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 100 dB SPL (125 Hz - 12500 Hz 1/3 octave bands)	29.3 Kg	R 9,947.37	R 11,340.00
<b>VERIS32-94</b>	3-way, 60Hz - 18kHz, 90° x 40° LF 1 x 12", MF 1 x 6.5", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 98 dB SPL (125 Hz - 12500 Hz 1/3 octave bands)	29.3 Kg	R 9,947.37	R 11,340.00

**VERSATILE INSTALLATION LOUDSPEAKERS / SOUND REINFORCEMENT**

**FULL RANGE SYSTEMS**

11 Ply Birch enclosure Dyna-Tech driver protection system, Ferrofluid-cooled HF driver, carbon ring cone LF, 16 gauge foam backed steel grille, 13 - M10 hang points, 4 Omnimount 60 bolt pattern, barrier strip / NL4 compatible locking connectors

<b>VERIS35-64</b>	3-way, 55Hz - 18kHz, 60° x 40° LF 1 x 15", MF 1 x 6.5", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 101 dB SPL (125 Hz - 12500 Ha 1/3 octave bands)	32.2 Kg	R 11,210.53	R 12,780.00
-------------------	---	---------	-------------	-------------

<b>VERIS35-64</b>	3-way, 55Hz - 18kHz, 90° x 40° LF 1 x 15", MF 1 x 6.5", HF 1 x 1", 200W RMS, 500W PGM 8 Ohm, black or white paint finish Recommended amp for maximum SPL: 420 to 600W @ 8 Ohms Sensitivity 1W/1m: 99 dB SPL (125 Hz - 12500 Ha 1/3 octave bands)	32.2 Kg	R 11,210.53	R 12,780.00
-------------------	--	---------	-------------	-------------

**SUBWOOFER SYSTEMS**

11 Ply Birch enclosure Dyna-tech driver protection system, Patented Cool-Coil LF Drivers, 16 gauge perforated steel Grille  
8 - M10 hang points, barrier strip and two locking connectors (NL4 type)

Model	Description	Weight	Excl VAT	Incl VAT
<b>VERIS210S</b>	Subwoofer, 40Hz - 500 Hz 2 x 10" 300W RMS, 750W PGM, 4 Ohm 8 - M10 hang points, black or white paint finish Recommended amp for maximum SPL: 630W to 900W @ 4 Ohms Sensitivity 1W/1m: 93 dB SPL (63 Hz - 160 Hz 1/3 octave bands)	28.6Kg	R 7,894.74	R 9,000.00

<b>VERIS212S</b>	Subwoofer, 37Hz - 500 Hz 2 x 12" 300W RMS, 750W PGM, 4 Ohm 8 - M10 hang points, black or white paint finish Recommended amp for maximum SPL: 630W to 900W @ 4 Ohms Sensitivity 1W/1m: 95 dB SPL (63 Hz - 160 Hz 1/3 octave bands)	36.1 Kg	R 9,157.89	R 10,440.00
------------------	---	---------	------------	-------------

15-Jan-12

**VERIS ACCESSORIES AND MOUNTING BRACKETS**

Model	Description	Weight	Excl VAT	Incl VAT
<b>VB - Y12</b>	VB - Y12 Yoke Bracket for Veris12 loudspeaker	5 Kg	R 947.37	R 1,080.00
<b>VB - Y15</b>	VB - Y15 Yoke Bracket for Veris15 loudspeaker	5.4 Kg	R 1,073.68	R 1,224.00
<b>VB - Y32</b>	VB - Y32 Yoke Bracket for Veris32 loudspeaker	5.4 Kg	R 1,231.58	R 1,404.00
<b>VB - Y35</b>	VB - Y35 Yoke Bracket for Veris35 loudspeaker	5.4 Kg	R 1,389.47	R 1,584.00
<b>VB - TILT</b>	Veris Tilting bracket - Can be attached to Yoke Brackets	1.4 Kg	R 473.68	R 540.00
<b>VB - VST</b>	Versatile Bracket for mounting single speaker to ceiling	2.7 Kg	R 852.63	R 972.00
<b>VFKIT</b>	Vertical flying kit for Veris 12 / 15 / 32 /35	2.3 Kg	R 789.47	R 900.00
<b>M6EYBLTKIT</b>	6mm Eyebolt kit - 4 eyebolts	0.5 Kg	R 473.68	R 540.00

# COMMUNITY PRICE LIST

# VLF SERIES

Suggested Retail Price  
15-Jan-12

## VERSATILE LOW FREQUENCY SERIES

### COMPACT VLF212 AND VLF208 BANDPASS SUBWOOFERS

Low profile, compact birch plywood enclosure, DYNA-TECH™ driver protection system, no grille design  
foam backed steel grille, 13 - M10 hang points, 4 Omnimount 60 bolt pattern, barrier strip / NL4 compatible locking connectors

Model	Description	Weight	Excl VAT	Incl VAT
VLF212BI	VLF212 - Black / Install 2 x 12" Compact Bandpass Subwoofer 45 Hz - 160 Hz (processed), 300W RMS, 750W PGM, 4 Ohms No grille design, slot loaded woofers, 12 M10 hang points 504mm x 552mm x 504mm	43.1Kg	R 9,947.37	R 11,340.00
VLF212WI	VLF212-White - Install			
VLF212BP	VLF212 - Black / Portable Same as VLF212BI with built in Ergo grip handles, rubber feet, pole mount socket, eight 10mm hang points, 2 x NL4 compatible locking connectors, 2 ¼-inch sockets		R 10,894.74	R 12,420.00
VLF208B	VLF208 - Black / Install Dual 8" bandpass micro subwoofer 60 Hz - 160 Hz (processed) 300W RMS, 750W PGM, 4 ohms No grille design, ultra compact, 8 x M10 hang points 210mm x 552mm x 330mm	21 Kg	R 7,421.05	R 8,460.00
VLF208W	White version of VLF208B			

### HIGH PERFORMANCE DIRECT RADIATING SUBWOOFER SYSTEMS

Versatile, high performance, slim profile, small footprint. Durable solid birch plywood enclosure (VLF208LV) or 18mm Baltic birch enclosure (VLF115, VLF118 and VLF218, heavy duty perforated steel grille.

Model	Description	Weight	Excl VAT	Incl VAT
VLF208LV-BI	VLF208 Large Volume - Black Install Dual 8" large volume compact subwoofer 30 Hz - 1000 Hz, 400W RMS, 1000W PGM, 4 ohms Low profile design, 12 x M10 hang points	26.3 Kg	R 9,000.00	R 10,260.00
VLF208LV-WI	White version of VLF208 LV-BI			
VLF208LV-BP	Portable version of VLF208LV with Ergo-Grip™ handle, rubber feet, pole mount socket, 8 x M10 hang points		R 9,789.47	R 11,160.00

# COMMUNITY PRICE LIST

# VLF SERIES

Suggested Retail Price  
15-Jan-12

---

## VERSATILE LOW FREQUENCY SERIES

---

### HIGH PERFORMANCE DIRECT RADIATING SUBWOOFER SYSTEMS

---

Model	Description	Weight	Excl VAT	Incl VAT
VLF115-BI	VLF115 Single 15" subwoofer system for install 26 Hz - 1000Hz, 600W RMS, 1500W PGM, 8 Ohm 16 x M10 hang points, black paint finish	38.1 Kg	R 21,000.00	R 23,940.00
VLF115-WI	White version of VLF115BI			
VLF115-BP	Portable version of VLF115BI with Ergo-Grip™ handles, rubber feet, pole mount socket and 4 x foot recesses on top of cabinet		R 22,263.16	R 25,380.00

---

Model	Description	Weight	Excl VAT	Incl VAT
VLF118-BI	VLF115 Single 18" subwoofer system for install 25 Hz - 1000Hz, 800W RMS, 2000W PGM, 8 Ohm 16 x M10 hang points, black paint finish	50.3 Kg	R 23,526.32	R 26,820.00
VLF118-WI	White version of VLF118BI			
VLF118-BP	Portable version of VLF118BI with Ergo-Grip™ handles, rubber feet, pole mount socket and 4 x foot recesses on top of cabinet		R 24,789.47	R 28,260.00

---

### VLF218 DUAL 18" SUBWOOFER SYSTEM

---

Low frequency dual 18" subwoofer systems for touring, rental and permanent installations. Active air and vented pole cooling

---

Model	Description	Weight	Excl VAT	Incl VAT
VLF218	Dual 18" Low Frequency Subwoofer System 30 Hz - 250 Hz, 1600W RMS / 4000W PGM, 4 Ohm Active Air and vented pole cooling Black paint finish Stacking feet and cups, Ergo grip handles	103.9 Kg	R 41,842.11	R 47,700.00

---

# COMMUNITY PRICE LIST

# WET SERIES II

Suggested Retail Price

15-Jan-12

## ALL WEATHER / ALL PURPOSE SOUND REINFORCEMENT / PLAYBACK LOUDSPEAKERS

### FULL RANGE WEATHER RESISTANT SYSTEMS

Multi-Layer Glass Composite Construction, Passive Crossover with PowerSense™ DDP 3-layer Weather-Stop™ Stainless Steel Grille, 1/2"-13 Mounting Points, Gland Nut with 3.6m SJOW Input Cable. Five year transferable warranty / Fifteen year enclosure warranty

Model	Description	Weight	Excl VAT	Incl VAT
<b>W2-218</b>	2 way, 70 Hz - 18 kHz, 80° H x 60° V LF 1 x 8" carbon fibre, HF 1 x 1" compression driver 125W RMS, 300W PGM, 8 Ohm stainless steel bracket included. Black finish	10 Kg	R 11,842.11	R 13,500.00
<b>W2-218W</b>	White version of WET218			
<b>W2-218T</b>	Same as WET218 with Built in 100W autoformer for 70/100V lines with selectable taps @ 100W, 50W, 25W, 12.5W	12 Kg	R 12,473.68	R 14,220.00
<b>W2-218WT</b>	White version of WET218W			
<b>W2-228</b>	Quasi 3 way, 70Hz - 18 kHz, 85° H x 85° V LF 1 x 8" carbon fibre, LF/MF 1 x 8" carbon fibre HF 1 x 1" compression driver 250W RMS, 600W PGM, 4Ohm stainless steel bracket included, black or white	18.1 Kg	R 20,052.63	R 22,860.00
<b>W2-228T</b>	Same as WET228 with built in 200W autoformer for 70/100V lines with selectable taps @ 200W, 100W, 50W, 25W	20 Kg	R 20,684.21	R 23,580.00
<b>W2-2V8</b>	2 way, 80Hz - 18 kHz Asymmetrical coverage: 70° - 120° H x 75° V LF 2 x 8", HF 1 x 1" compression driver 250W RMS, 600W PGM, 4 Ohm stainless steel bracket included	21.8 Kg	R 20,052.63	R 22,860.00
<b>W2-2V8W</b>	White version of WET2V8	21.8 Kg	R 22,578.95	R 25,740.00
<b>W2-2V8T</b>	Same as WET2V8 with built in 200W autoformer for 70/100V lines with selectable taps @ 200W, 100W, 50W, 25W	23.6 Kg	R 20,684.21	R 23,580.00
<b>W2-V8WT</b>	White version of WET2V8T	23.6 Kg	R 23,210.53	R 26,460.00
<b>W2-2W8</b>	2 way, 80Hz - 18 kHz, 120° H x 60° V LF 2 x 8" carbon fibre, HF 1 x 1" Compression driver 250W RMS, 600W PGM, 4 ohm stainless steel bracket included, black or white	20 Kg	R 20,052.63	R 22,860.00
<b>W2-2W8T</b>	Same as WET2W8 with built in 200W autoformer for 70/100V lines with selectable taps @ 200W, 100W, 50W, 25W	18.2 Kg	R 20,684.21	R 23,580.00
<b>W2-215-99</b>	2 way, 50 Hz - 20 kHz, 90° H x 90° V LF 1 x 15" carbon fibre, HF 1 x 1.5" compression driver 200W RMS, 600W PGM, 8 Ohm	61.3 Kg	R 52,894.74	R 60,300.00

# COMMUNITY PRICE LIST

# WET SERIES II

Suggested Retail Price  
15-Jan-12

## FULL RANGE WEATHER RESISTANT SYSTEMS

Multi-Layer Glass Composite Construction, Passive Cross-Over with PowerSense™ DDP, 3 Layer Weather Stop™ Stainless Steel Grille, 1/2"-13 Mounting Points, Gland Nut with 3.6m SJOW Input Cable

<b>W2-315-64H</b>	3-way, 60 Hz - 18 kHz, 60° H x 40° V LF 1 x 15", MF 1 x 2" M200, HF1 x 1" VHF100 200W RMS, 500W PGM, 4 Ohm	60 Kg	R 54,473.68	R 62,100.00
<b>W2-315-94H</b>	Same as WET315-64H with 90° H x 40° V  Also available in white			

Model	Description	Weight	Excl VAT	Incl VAT
<b>W2-322L-64H</b>	3-way, 50 Hz - 18 kHz, 60° H x 40° V (biamp only) LF 2 x 12", MF 1 x EM280, HF 1 x 1" VHF100 LF 400W RMS, 1000W PGM, 4 Ohm Mid/High 160W RMS, 400W PGM, 4 Ohm	73.5 Kg	R 75,000.00	R 85,500.00
<b>W2-322L-94H</b>	Same as WET322L-64H with 90° H x 40° V  Also available in white			

## WET SUBWOOFER WEATHER RESISTANT SYSTEMS

Multi-Layer Glass Composite Construction, 3 Layer Weather-Stop™ Grille, 1/2"-13 Mounting Points, Gland Nut with 3.6 m SJOW input cable

Model	Description	Weight	Excl VAT	Incl VAT
<b>W2-112</b>	Subwoofer, 40 Hz - 700 Hz LF 1 x 12", 200W RMS, 500W PGM, 8 Ohm	27 Kg	R 28,263.16	R 32,220.00
<b>SSY25</b>	654mm long stainless steel bracket for WET112	3.8 Kg	R 2,210.53	R 2,520.00
<b>W2-122</b>	Subwoofer, 35 Hz - 600 Hz LF 2 x 12", 400W RMS, 1000W PGM, 4 Ohm	56 Kg	R 42,473.68	R 48,420.00
<b>W2-125</b>	Subwoofer, 30 Hz - 1 kHz LF 2 x 15", 400W RMS, 1000W PGM, 4 Ohm	60 Kg	R 49,578.95	R 56,520.00

# COMMUNITY PRICE LIST

# LINE TRANSFORMERS

Suggested Retail Price  
15-Jan-12

---

## TRANSFORMERS FOR 70V, 100V AND 140V LINES

---

### LOUDSPEAKER LINE TRANSFORMERS

True Transformers with Full electrical Isolation, High Permeability Cores, Multi-Tap Capability, Open Frame Construction

---

Model	Description	Weight	Excl VAT	Incl VAT
<b>TRC400</b>	Transformer for 70V, 100V, 140V lines 400W @ 4 Ohms, 200W @ 8 Ohms taps for full 1/2, 1/4 and 1/8 power	4.5 Kg	R 2,936.84	R 3,348.00
<b>AFC200</b>	Autotransformer for 70v and 100v lines 200W @ 4 or 8 Ohms taps for full 1/2, 1/4 and 1/8 power	0.9 Kg	R 1,642.11	R 1,872.00

---

# COMMUNITY PRICE LIST

**DSPEC**

Suggested Retail Price  
15-Jan-12

## DSPEC: Digital speaker protection, Enhancement & Control

Networked Loudspeaker Processor

Model	Description	Weight	Excl VAT	Incl VAT
<b>dSPEC226</b>	<b>2 Analogue Inputs, 6 Analogue Outputs</b> Loudspeaker management system with 2 analogue inputs and 6 analogue outputs, 115 dB dynamic range, Community DSL Library, CONEQ™ inverse power correction, FIR filters, Effortless Ethernet network setup. Each output protects peak, program and long term	2.9 Kg	R 26,052.63	R 29,700.00
<b>dSPEC226AN</b>	<b>4 Analogue Inputs, 6 Analogue Outputs</b> Same as dSPEC226 with a total of 4 analogue inputs via an analogue expansion card, and 6 analogue outputs	2.9 Kg	R 29,210.53	R 33,300.00
<b>dSPEC226AE</b>	<b>2 Analogue Inputs, 6 Analogue Outputs, 2 AES3 Input Pairs</b> Same as dSPEC226 with 2 analogue inputs, 6 analogue outputs and 2 AES3 dual channel digital inputs via a second expansion card. Provides options for 4 x digital inputs as well as the 2 analogue inputs	2.9 Kg	R 32,368.42	R 36,900.00
<b>dSPEC226CO</b>	<b>2 Analogue Inputs, 6 Analogue Outputs, Cobranet™</b> Same as dSPEC226 with a CobraNet™ expansion card, providing for a selection of 8 digital inputs and 8 digital outputs, while the 2 analogue inputs and 6 analogue outputs remain active and addressable	2.9 Kg	R 33,947.37	R 38,700.00

### dSPEC ACCESSORIES

Model	Description	Weight	Excl VAT	Incl VAT
<b>RLC1</b>	Remote level control, to change volume settings from a remote location using the dSPEC's control ports. A port is provided for each of the 6 outputs		R 1,010.53	R 1,152.00
<b>RPS4</b>	Remote preset recall switch, allows up to 4 presets to be recalled from a remote location using the dSPEC's control ports		R 2,052.63	R 2,340.00

### dSPEC SOFTWARE

Model	Description	Weight	Excl VAT	Incl VAT
<b>Resyn™</b>	dSPEC control software for configuring and managing multiple dSPEC systems over an Ethernet network. Engineered workflow walks the user through the process of selecting loudspeaker types and models, labelling inputs and outputs, setting protection levels, establishing system EQ delay and limiting, configuring user presets, and creating access passwords  Download the software at <a href="http://www.communitypro.com/dspec">www.communitypro.com/dspec</a> .		Free	Free